

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
28 December 2000 (28.12.2000)

PCT

(10) International Publication Number
WO 00/79545 A1

(51) International Patent Classification⁷: **H01B 7/00**,
11/04, 11/08, 11/10

(74) Agent: **CONTE, Robert, F., I.**; Lee, Mann, Smith,
McWilliams, Sweeney & Ohlson, P.O. Box 2786, Chicago,
IL 60690 (US).

(21) International Application Number: **PCT/US00/16420**

(22) International Filing Date: **14 June 2000 (14.06.2000)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
60/139,927 18 June 1999 (18.06.1999) US
60/141,462 29 June 1999 (29.06.1999) US

(81) Designated States (*national*): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **BELDEN WIRE & CABLE COMPANY** [US/US]; 2200 U.S. Highway 27 South, Richmond, IN 47374 (US).

Published:


— With international search report.

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **GAREIS, Galen, M.** [US/US]; 420 South 19th Street, Richmond, IN 47374 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **HIGH PERFORMANCE DATA CABLE**



(57) Abstract: An improved high performance twisted pair data cable (20) that has an impedance standard deviation of less than 3.5 when the standard deviation is calculated around an average impedance of 50 to 200 ohms and preferably 90 to 110 ohms. The twisted pair is helically wrapped with a metal shield tape (16) at a tension that provides a cross-sectional void of less than 25 % and preferably less than 18 % of the cross-sectional area of the shielded twisted pair cable. The tape is helically wrapped with an overlap of 30-45 % and at an angle of 35-45 degrees with respect to the longitudinal axis of the cable. The cable has a rating up to 600 MHz.



WO 00/79545 A1